

Serial No. 09/932,629 - Howard Lee
Amendment of 3/17/2003

Page 3

AMENDMENTS TO THE CLAIMS

What is claimed as being new and desired to be protected by LETTERS PATENT of the United States is as follows:

1. (Amended) A ~~sure grip screwdriver screwdriver/fastener~~ system for ~~allowing a user to screw and unscrew threaded fasteners in a convenient and efficient manner~~ comprising, in combination:

a shaft fabricated of a rigid metallic material in a cylindrical configuration with an axis and having a handle end and a working end, the shaft having a working inner portion adjacent to the handle end and a working outer portion adjacent to the working end and with a flat cut face on the outermost extent of the working end perpendicular to the axis of the shaft, the working outer portion having a generally cube-shaped configuration with a square cross section and an axial length of a first smaller size adjacent to the face, the working inner portion having a generally cube-shaped configuration with a square cross section and an axial length of a second larger size adjacent to the working outer portion, with a bevel adjacent to the working inner portion remote from the face;

a screwdriver handle having a shaft end and a gripping surface end, the shaft end having a generally cylindrical recess to securely receive and retain in one position the handle end of the shaft and with the gripping surface end having a plurality of

Serial No. 09/932,629 - Howard Lee
Amendment of 3/17/2003

Page 4

axial indentations to facilitate the user's grip of the system; and

a threaded fastener having a threaded portion and a head portion, the threaded portion having threads for coupling to a recipient surface upon rotation and with the head portion having a cylindrical configuration with a central stepped recess, the stepped recess having a cube-shaped interior reception area and an exterior cube-shaped reception area with the interior reception area being smaller to snugly receive the working outer portion of the shaft and with the exterior reception area being larger to snugly receive the working inner portion of the shaft and alternatively, wherein the threaded fastener is of a smaller size, the working outer portion is snugly receivable by the working outer portion and, alternatively, wherein the working portions are of a larger size, the working outer portion is snugly receivable by the working outer portion.

2. (Three Times Amended) ~~A flat ended, double cube shaped tipped, screwdriver~~ screwdriver/fastener system comprising:

a shaft having a handle end and a working end, the shaft having a working inner portion adjacent to the handle end and a working outer portion adjacent to the working end, the working outer portion having a generally cube-shaped configuration of a first smaller size with a flat outermost tip being perpendicular

Serial No. 09/932,629 - Howard Lee
Amendment of 3/17/2003

Page 5

to the shaft, the working inner portion having a generally cube-shaped configuration of a second larger size;

a shaft support with a recess at one end to receive the handle end of the shaft; and

a threaded fastener having a threaded portion and a head portion, the head portion having a cylindrical configuration with a central stepped recess, the stepped recess having a cube-shaped interior reception area with a flat innermost portion and an exterior cube-shaped reception area with the interior reception area being smaller to snugly receive the working outer portion of the shaft and the flat innermost portion allowing a positive alignment of the fastener and the working tip and with the exterior reception area being larger to snugly receive the working inner portion of the shaft.

3. (Previously Canceled)
4. (Cancel)
5. (Previously Canceled)
6. (Cancel)